



SNA7108 Hardware Appliance

POWERFUL AND EASY TO USE ADC



The complete solution for those seeking immediate performance. **SKUDONET SNA7108 Hardware Appliance** provides pre-configured hardware with its software already installed, offering a turnkey solution.

This **physical load balancer** combines advanced cybersecurity, high availability, and easy management, all in one device designed to meet the most demanding needs. Perfect for critical installations where stability and simplicity are paramount.



Massive Scalability

- Supports up to **40Gbps** of traffic throughput.
- Load balancing at **Layers 2, 3, 4, and 7 for WAN** uplinks, applications, services, and data centers.
- Advanced traffic distribution methods: weight-based, round robin, hashing, least connections, least response time, and symmetric distribution.
- Configurable persistence and session management, including **session replication in stateful clusters**.
- Inter-data center WAN load balancing with DNS-based **Global Server Load Balancing (GSLB)**.
- Automated and **customizable health checks** for servers and services.



Security

- Integrated Web Application Firewall (**WAF**) with **OWASP** rules for SQL injection (**SQLi**), cross-site scripting (**XSS**), botnet detection, and other application-layer threats.
- Support for custom **WAF rule files** and personalized error responses for blocked requests.
- **DDoS protection** engine with configurable per-service rules.
- Real-time and **automated threat intelligence** with over 200 preloaded blacklists, including botnets, spam lists, TOR nodes, anonymous proxies, and brute force hosts.
- **Role-Based Access Control (RBAC)** with LDAP/AD integration and SSH access control for administrators.
- **Full VPN support**: site-to-site IPsec, L2TP+IPsec, and remote server warrior mode.
- **Secure SSL/TLS support** with automatic Let's Encrypt certificate management.
- Compliance-ready with **A+ SSL Labs** rating and **PCI DSS** standards.



System

- Operating System upgraded to **Debian 12.5 LTS** for extended stability and support.
- **Optimized kernel** (6.1.90-10skudonet) for improved performance and networking capabilities.
- High availability with active-passive **clustering and stateful failover**, ensuring no session loss during node transitions.
- Enhanced logging and monitoring: **profiling logs for HTTP/S farms**, user-friendly log viewers, and extended IPDS filter logs.
- Centralized **Web Console with a Angular v18** interface, featuring improved UX, dark mode, and multi-language support.
- Fully programmable **REST+JSON API** for automation and integration.
- Support for **multiple network protocols** including TCP, UDP, SCTP, SIP, FTP, TFTP, HTTP, HTTPS, RDP, SSH, POP3, IMAP, SMTP, DNS, NTP, LDAP, LDAPS, Radius, WebSocket, and more.



Management

- **Advanced routing:** dNAT, sNAT, DSR, stateless dNAT, and custom static routing.
- **VLAN and Virtual IP** support for flexible network configurations.
- **Real-time block lists (RBL)** and Domain Name System-based Blackhole List (DNSBL) integration.
- Enhanced **SNMP monitoring** with multiple scope support.
- Session synchronization daemon improvements for **cluster stability**.

What About Performance?



+10 MILLION

concurrent users per
sec in layer 4



+140 THOUSAND

concurrent users per
sec in layer 7 HTTP



+120 THOUSAND

concurrent users per
sec in layer 7 HTTPS

5,720,000

TCP REQUESTS/SEC

320,000

HTTP REQUESTS/SEC

195,000

HTTPS REQUESTS/SEC



Appliance I/O



Hardware Specifications

CPU	Intel® Core™ i5-9500, Base Frequency 3.00 GHz with 6 cores
Memory	8GB DDR4 2667 MHz (max. 32GB)
LAN	8 x Intel i210 GbE RJ45
Storage	32 GB mSATA
Console	1 x RJ45
Expansion Slot	1 x PCIe
USB	2 x USB 3.0
Power Supply	220W single power supply unit, AC 90~264V@47~63Hz
Dimensions	1U: 438(W) x 44(H) x 321(D) mm, or 17.2"(W) x 1.73"(H) x 12.63"(D)
Weight	8.5 kg
Operating Temperature	0 ~ 40°C, or 32°F ~ 104°F
Storage Temperature	-20° ~ 70°C, or -4°F ~ 158°F
Operating Humidity	5 ~ 90%, non-condensing
Cooling System	2 cooling silent fans
Certification EMC	CE Class A, FCC Class A, RoHS
IPMI	No



Caption

F1	LED indicators
F2	LCM
F3	Keypad
F4	Console
F5	USB 3.0
F6	LAN, 8 x RJ-45 Gbe
F7	NIC Expansion Module
R1	1 x PCIe expansion slot (optional)
R2	Cooling fans
R3	Power on/off switch
R4	Single power supply

Optional Expansion Modules

E801	8 ports x 1Gb RJ45
F240	2 ports x 40Gb QSFP
F410	4 ports x 10Gb SFP

MORE THAN 500

Customers worldwide

MORE THAN 60

Countries

MORE THAN 90%

Support renewal rate

Contact us at info@skudonet.com

Visit our website [SKUDONET.com](https://www.skudonet.com)

DISCLAIMER: This document is strictly private, confidential and personal to its recipients and should not be copied, distributed or reproduced in whole or in part, nor passed to any third party.

Copyright © SKUDONET SL. All rights reserved.